

Classe 5

IT-EN

5

Classe

5



**RANCILIO CLASSE 5:
LA BELLEZZA DELLA SEMPLICITÀ**

Minimalismo funzionale di ispirazione industriale e un'estetica contemporanea rappresentano il punto di forza di Classe 5. Una macchina che trasforma l'essenzialità e l'eleganza in caratteristiche distintive.

ESTETICA E SOLIDITÀ

Fiancate moderne e ricercate, ampi coprigruppi ed ergonomia dell'area lavoro garantiscono al barista un utilizzo semplice e confortevole. La tecnologia Metal Dome applicata alla pulsantiera assicura un click-feeling armonico e gradevole.

INTUITIVITÀ E IMMEDIATEZZA

Anche per questa classe abbiamo applicato l'avanzata tecnologia USB che consente una rapida e precisa gestione dei principali settaggi macchina. La pulsantiera con icone retroilluminate da luci bianche a LED rendono il suo utilizzo altamente funzionale.

GREEN ATTITUDE

La razionalizzazione di tutte le fasi del processo di industrializzazione relativo alla componentistica interna ed esterna testimoniano il concreto impegno ecologico e ambientale che Rancilio Group persegue lungo l'intera filiera produttiva.

CUSTOMER SUPPORT SEMPLICE E VELOCE

La maggior parte delle operazioni di assistenza tecnica potranno essere svolte da fronte macchina, rimuovendo con grande disinvoltura e facilità operativa la bacinella o il pannello frontale.

UNA GAMMA COMPLETA E VERSATILE

Da 2 a 3 gruppi erogatori, USB o semiautomatica, nero antracite o bianco ghiaccio. Classe 5 è una macchina in grado di mettere a frutto con intelligenza i progressi tecnologici e risultare estremamente competitiva nel suo segmento.

**RANCILIO CLASSE 5:
THE CHARM OF SIMPLICITY**

Industrially inspired functional minimalism and a contemporary aesthetics are the strong points of Classe 5. A machine that transforms basic essential and elegance into distinctive personality traits.

AESTHETICS AND RELIABILITY

Modern and sophisticated side panels, ample groupcovers and an ergonomic working area guarantee baristas comfort and convenience. The Metal Dome technology applied to the keypad ensures a pleasant, harmonious touch sensation.

INTUITIVE AND INSTANT

For this classe too we have used a high-tech USB system enabling the main machine settings to be managed quickly and precisely. The keypad with icons backlit with white LED lights makes it extremely functional.

GREEN ATTITUDE

Every stage of the manufacturing process for both the internal and external components bears witness to the Rancilio Group's practical commitment to the environment throughout the supply chain.

QUICK AND EASY CUSTOMER SUPPORT

Most maintenance operations can be done quite simply from the front of the machine just by removing the easy to handle drip tray or front panel.

A COMPLETE VERSATILE RANGE

From 2 to 3 brewing units, USB or semi-automatic versions, anthracite black or ice white, Classe 5 makes the very best, most intelligent use of advances in technology, resulting in a machine that beats its competitors hands down.





CLASSE 5 USB

CARATTERISTICHE TECNICHE

Scambiatori di calore indipendenti
Riscaldamento elettrico
Pompa volumetrica incorporata
Manometro controllo pressione caldaia
Manometro controllo pressione pompa
Controllo pressione caldaia con pressostato
Computer di bordo multifunzione e porta USB
Versione standard e versione COMPACT

DOTAZIONI STANDARD

3GR: 2 portafiltro per due caffè e 1 portafiltro per un caffè / 2GR: 1 portafiltro per due caffè e 1 portafiltro per un caffè, 2 erogatori vapore, 1 erogatore acqua calda, dischi per lavaggio, piedini rialzabili

DOTAZIONI A RICHIESTA

C-Lever - comando vapore ergonomico, YouSteam - comando vapore manuale (*), adattatore cialde e capsule, scaldatazze elettrico.

ACCESSORI

Addolcitore d'acqua, Macinadosatore

MATERIALI

Acciaio inox satinato e pannelli in ABS e nylon

COLORI

Nero antracite e bianco ghiaccio

TECHNICAL FEATURES

*Independent heat exchangers
Electrical heating
Built-in volumetric pump
Boiler pressure control gauge
Pump pressure control gauge
Boiler pressure control with pressurestat
Multifunction on-board computer and USB port
Standard and COMPACT version*

STANDARD FEATURES

3GR: 2 filter-holder for two coffees and 1 filter-holder for one coffee / 2GR: 1 filter-holder for two coffees and 1 filter-holder for one coffee, 2 steam wands, 1 hot water dispenser, cleaning discs, adjustable feet

EXTRA FEATURES ON REQUEST

C-Lever - ergonomic steam control, YouSteam - manual steam wand (), pods and caps adaptor, electric cup warmer*

ACCESSORIES

Water softener, Dosing grinder

MATERIALS

Brushed stainless steel, ABS and nylon panels

COLOURS

Anthracyte black and Ice white

CLASSE 5USB 2GR

Dimensioni (L×P×A) - Dimensions (W×D×H) 770×540×520 mm - 30.3×21.3×20.5 in	Peso - Weight 55 kg - 121.2 lb
Potenza caldaia - Boiler power 2700 W (120 V) - 4300 W	Caldaia - Boiler 11 l - (2.4 gal _{UK})
Voltaggio - Voltage 120 V / 220-240 V / 380-415 V (3N)	Frequenza - Frequency 50/60 Hz

CLASSE 5USB 2GR COMPACT

Dimensioni (L×P×A) - Dimensions (W×D×H) 610x540x520 mm - 24.0×21.3×20.5 in	Peso - Weight 48 kg - 105.8 lb
Potenza caldaia - Boiler power 2700 W (120 V) - 3000 W	Caldaia - Boiler 5 l - (1.1 gal _{UK})
Voltaggio - Voltage 120 V / 220-240 V / 380-415 V (3N)	Frequenza - Frequency 50/60 Hz

CLASSE 5USB 3GR

Dimensioni (L×P×A) - Dimensions (W×D×H) 1010x540x520 mm - 39.8×21.3×20.5 in	Peso - Weight 70 kg - 154.3 lb
Potenza caldaia - Boiler power 6000 W	Caldaia - Boiler 16 l - (3.5 gal _{UK})
Voltaggio - Voltage 220-240 V / 380-415 V (3N)	Frequenza - Frequency 50/60 Hz

A RICHIESTA | ON DEMAND

	C-LEVER STEAM		CLOUD CONNECT		PODS & CUPS
	YOU-STEAM (*)		CUP WARMER		

(*) non disponibile per 2GR COMPACT
not available for 2GR COMPACT



CLASSE 5 S

CARATTERISTICHE TECNICHE

Scambiatori di calore indipendenti
Riscaldamento elettrico
Pompa volumetrica incorporata
Manometro controllo pressione caldaia
Manometro controllo pressione pompa
Controllo pressione caldaia con pressostato
Versione standard e versione COMPACT

DOTAZIONI STANDARD

3GR: 2 portafiltro per due caffè e 1 portafiltro per un caffè / 2GR: 1 portafiltro per due caffè e 1 portafiltro per un caffè, 2 erogatori vapore, 1 erogatore acqua calda, dischi per lavaggio, piedini rialzabili

DOTAZIONI A RICHIESTA

C-Lever - comando vapore ergonomico, youSteam - comando vapore manuale (*), adattatore cialde e capsule, scaldatazze elettrico, riscaldamento a gas (*)

ACCESSORI

Addolcitore d'acqua, Macinadosatore.

MATERIALI

Acciaio inox satinato e pannelli in ABS e nylon

COLORI

Nero antracite e bianco ghiaccio

TECHNICAL FEATURES

*Independent heat exchangers
Electrical heating
Built-in volumetric pump
Boiler pressure control gauge
Pump pressure control gauge
Boiler pressure control with pressurestat
Standard and COMPACT version*

STANDARD FEATURES

3GR: 2 filter-holder for two coffees and 1 filter-holder for one coffee / 2GR: 1 filter-holder for two coffees and 1 filter-holder for one coffee, 2 steam wands, 1 hot water dispenser, cleaning discs, adjustable feet

EXTRA FEATURES ON REQUEST

C-Lever - ergonomic steam control, youSteam - manual steam wand (), pods and caps adaptor, electric cup warmer, gas heating (*)*

ACCESSORIES

Water softener, Dosing grinder

MATERIALS

Brushed stainless steel, ABS and nylon panels

COLOURS

Anthracyte black and Ice white

CLASSE 5S 2GR

Dimensioni (L×P×A) - Dimensions (W×D×H) 770×540×520 mm - 30.3×21.3×20.5 in	Peso - Weight 55 kg - 121.2 lb
Potenza caldaia - Boiler power 2700 W (120 V) - 4300 W	Caldaia - Boiler 11 l - (2.4 gal _{UK})
Voltaggio - Voltage 120 V / 220-240 V / 380-415 V (3N)	Frequenza - Frequency 50/60 Hz

CLASSE 5S 2GR COMPACT

Dimensioni (L×P×A) - Dimensions (W×D×H) 610x540x520 mm - 24.0×21.3×20.5 in	Peso - Weight 48 kg - 105.8 lb
Potenza caldaia - Boiler power 2700 W (120 V) - 3000 W	Caldaia - Boiler 5 l - (1.1 gal _{UK})
Voltaggio - Voltage 120 V / 220-240 V / 380-415 V (3N)	Frequenza - Frequency 50/60 Hz

CLASSE 5S 3GR

Dimensioni (L×P×A) - Dimensions (W×D×H) 1010x540x520 mm - 39.8×21.3×20.5 in	Peso - Weight 70 kg - 154.3 lb
Potenza caldaia - Boiler power 6000 W	Caldaia - Boiler 16 l - (3.5 gal _{UK})
Voltaggio - Voltage 220-240 V / 380-415 V (3N)	Frequenza - Frequency 50/60 Hz

A RICHIESTA | ON DEMAND

	C-LEVER STEAM		CUP WARMER		PODS & CUPS
	YOU-STEAM (*)		GAS HEATING (*)		

(*) non disponibile per 2GR COMPACT
not available for 2GR COMPACT

FEATURES STANDARD | STANDARD-FEATURES

	EASY CLEAN		SOFT TOUCH		GRID SYSTEM
	HYDRO HUB		ERGO FILTER HOLDER		

FEATURES STANDARD | STANDARD-FEATURES

	HYDRO HUB		GRID SYSTEM
	ERGO FILTER HOLDER		

(*) non disponibile per 2GR COMPACT
not available for 2GR COMPACT

CONTATTI / CONTACTS

HEADQUARTERS, PRODUCTION PLANT AND R&D CENTERS

Rancilio Group S.p.A. con socio unico

Viale della Repubblica 40
20015 Villastanza di Parabiago (MI) - Italy
Ph. +39 0331 408200
Fax +39 0331 551437
info@ranciliogroup.com

Egro Suisse AG

Bahnhofstrasse 66
5605 Dottikon - Switzerland
Ph. +41 (0)56 616 95 95
Fax +41 (0)56 616 95 97
info-ch@ranciliogroup.com

WORLDWIDE BRANCH LOCATIONS

Spain

Rancilio Group España, S.A.
Gran Vía de Carlos III, 84 3ª-Edificio Trade
08028 Barcelona - Spain
Ph. +34 902 884 275
Ph. +34 934 923 414
Fax +34 934 965 701
info-es@ranciliogroup.com

Portugal

Rancilio Group Portugal Lda
Rua José Vicente Gonçalves nº14-Armaz.-2
Parque Industrial do Seixal
2840-048 Aldeia de Paio Pires-Seixal
Lisboa - Portugal
Ph. +351 21 493 52 58

Centro de Negócios da Maia
Rua Albino José Domingues, n.º 683
4470-557 Maia - Porto - Portugal
Ph. + 351 22 490 39 77
info-pt@ranciliogroup.com

Germany

Rancilio Group Deutschland GmbH
Talstrasse 27
97990 Weikersheim - Germany
Ph. +49 7934 99 29 30
Fax +49 7934 99 29 330
info-de@ranciliogroup.com

Switzerland

Egro Suisse AG
Bahnhofstrasse 66
5605 Dottikon - Switzerland
Ph. +41 (0)56 616 95 95
Fax +41 (0)56 616 95 97
info-ch@ranciliogroup.com

USA/Canada

Rancilio Group North America Inc.
1340 Internationale Parkway / Suite 200
Woodridge, IL 60517 - U.S.A.
Ph. +1 630 914 7900
Fax +1 630 914 7901
Toll Free: +1 877 726 2454
info@ranciliogroupna.com

www.ranciliogroup.com



www.facebook.com/RancilioGroup



[Rancilio Group Channel](#)



<https://instagram.com/ranciliogroup/>



ITALIANO ENGLISH
COD. 90 011 197 | 03-2016